

IF IT WORX, IT'S



# PRODUCT OVERVIEW



# CONTENTS

## COLOUR SYSTEMS

A3 Multifunctional Systems .....	3
A4 Multifunctional Systems .....	6
A3 Print System .....	7
A4 Print Systems .....	8

## B/W SYSTEMS

A3 Multifunctional Systems .....	9
A4 Multifunctional Systems .....	13
A3 Print System .....	15
A4 Print Systems .....	16

## LARGE FORMAT COPY/PLOT SYSTEMS

.....	17
-------	----

# A3 MULTIFUNCTIONAL SYSTEMS



		CDC 5520	CDC 5525	CDC 1725
COPYING	Copy speed	20 A4 pages/min., 8/10 A3 pages/min. in colour and b/w	25 A4 pages/min., 9/13 A3 pages/min. in colour and b/w	25 A4 pages/min., 13 A3 pages/min. in colour and b/w
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256
	Standard paper feed	600 (500 + 100 sheets)	600 (500 + 100 sheets)	1,100 (2 x 500 + 100 sheets)
	Optional paper feed	1 or 2 x 500 sheets	1 or 2 x 500 sheets	2 x 500, 3,000 sheets
	Paper capacity, max	1,600 sheets	1,600 sheets	4,100 sheets
	Paper format	A6R–A3	A6R–A3	A6R–A3
	Original feeder	Standard	Standard	Option: DP-750 or DP-760
	Duplex	Standard	Standard	Standard
	System memory	1,024 MB RAM, max 2,048 MB RAM	1,024 MB RAM, max 2,048 MB RAM	2,048 MB + 80 GB
	Zoom	25%–400%	25%–400%	25%–400%
Cabinet	Option: no. 62	Option: no. 62	Option: no. 56	
PRINTING	Type	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2), CF slot	USB 2.0, 10/100/1000BaseTX, USB host (2), CF slot	10/100BaseTX, USB 2.0, USB host, CF slot
	Operating systems	Windows XP, Vista, Windows 7, Server 2003/2008 R2, Novell NetWare, Linux, Mac ex OS 10.x	Windows XP, Vista, Windows 7, Server 2003/2008 R2, Novell NetWare, Linux, Mac ex OS 10.x	Windows XP, Vista, Windows 7, Server 2003/2008, Novell NetWare, Linux, Mac ex OS 10.5
	Emulations	PCL6, KPDLL 3 (PS 3 compatible), XPS, PRESCRIBE IIc	PCL6, KPDLL 3 (PS 3 compatible), XPS, PRESCRIBE IIc	PCL6, KPDLL 3 (PS 3 compatible), XPS, PRESCRIBE IIc
NETWORK	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100BaseTX
	Network protocols	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk
	Operating systems	Windows XP, Vista, Windows 7, Server 2003/2008 R2	Windows XP, Vista, Windows 7, Server 2003/2008 R2	Windows XP, Vista, Windows 7, Server 2003/2008
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100BaseTX
	Network protocols	TCP/IP	TCP/IP	TCP/IP
FAX	Originals	max A3	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	100/200	100/200	100/2,000

# A3 MULTIFUNCTIONAL SYSTEMS



		CDC 1930	CDC 1935	CDC 1945	CDC 1950
COPYING	Copy speed	30 A4 pages/min., 15 A3 pages/min. in colour and b/w	35 A4 pages/min., 17 A3 pages/min. in colour and b/w	45 A4 pages/min., 22 A3 pages/min. in colour and b/w	50 A4 pages/min., 25 A3 pages/min. in colour, 55 A4 pages/min., 27 A3 pages/min. in b/w
	Copy resolution	600 x 600 dpi, 9,600 x 600 dpi level	600 x 600 dpi, 9,600 x 600 dpi level	600 x 600 dpi, 9,600 x 600 dpi level	600 x 600 dpi, 9,600 x 600 dpi level
	Greyscales	256	256	256	256
	Standard paper feed	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)
	Optional paper feed	2 x 500, 3,000 sheets, different combinations possible	2 x 500, 3,000 sheets, different combinations possible	2 x 500, 3,000 sheets, different combinations possible	2 x 500, 3,000 sheets, different combinations possible
	Paper capacity, max	7,150 sheets	7,150 sheets	7,650 sheets	7,650 sheets
	Paper format	A6R–A3+	A6R–A3+	A6R–A3+	A6R–A3+
	Original feeder	Option: DP-770 or DP-771	Option: DP-770 or DP-771	Option: DP-770 or DP-771	Option: DP-770 or DP-771
	Duplex	Standard	Standard	Standard	Standard
	System memory	2,048 MB RAM + 160 GB	2,048 MB RAM + 160 GB	2,048 MB RAM, 2 x 160 GB	2,048 MB RAM, 2 x 160 GB
	Zoom	25%–400%	25%–400%	25%–400%	25%–400%
Cabinet	Option: no. 63	Option: no. 63	Option: no. 63	Option: no. 63	
PRINTING	Type	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host, CF slot	USB 2.0, 10/100/1000BaseTX, USB host, CF slot	USB 2.0, 10/100/1000BaseTX, USB host, CF slot	USB 2.0, 10/100/1000BaseTX, USB host, CF slot
	Operating systems	Windows XP, Vista, Windows 7, Server 2003/2008 R2, Novell NetWare, Linux, Mac ex OS 10.4	Windows XP, Vista, Windows 7, Server 2003/2008 R2, Novell NetWare, Linux, Mac ex OS 10.4	Windows XP, Vista, Windows 7, Server 2003/2008 R2, Novell NetWare, Linux, Mac ex OS 10.4	Windows XP, Vista, Windows 7, Server 2003/2008 R2, Novell NetWare, Linux, Mac ex OS 10.4
	Emulations	PCL6, KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6, KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6, KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6, KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc
NETWORK	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host, CF slot	USB 2.0, 10/100/1000BaseTX, USB host, CF slot	USB 2.0, 10/100/1000BaseTX, USB host, CF slot	USB 2.0, 10/100/1000BaseTX, USB host, CF slot
	Network protocols	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk
	Operating systems	Windows XP, Vista, Windows 7, Server 2003/2008 R2	Windows XP, Vista, Windows 7, Server 2003/2008 R2	Windows XP, Vista, Windows 7, Server 2003/2008 R2	Windows XP, Vista, Windows 7, Server 2003/2008 R2
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	Originals	max A3	max A3	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	100/2,000	100/2,000	100/2,000	100/2,000

# A3 MULTIFUNCTIONAL SYSTEMS



		CDC 1965	CDC 1970
COPYING	Copy speed	65 A4 pages/min., 32 A3 pages/min. in colour and b/w	70 A4 pages/min., 35 A3 pages/min. in colour, 75 A4 pages/min., 37 A3 pages/min. in b/w
	Copy resolution	600 x 600 dpi, 9,600 x 600 dpi level	600 x 600 dpi, 9,600 x 600 dpi level
	Greyscales	256	256
	Standard paper feed	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)
	Optional paper feed	2 x 500, 3,000 sheets, different combinations possible	2 x 500, 3,000 sheets, different combinations possible
	Paper capacity, max	7,650 sheets	7,650 sheets
	Paper format	A6R-A3+	A6R-A3+
	Original feeder	Standard	Standard
	Duplex	Standard	Standard
	System memory	2,048 MB RAM, 2 x 160 GB	2,048 MB RAM, 2 x 160 GB
	Zoom	25%-400%	25%-400%
Cabinet	--	--	
PRINTING	Type	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host, CF slot	USB 2.0, 10/100/1000BaseTX, USB host, CF slot
	Operating systems	Windows XP, Vista, Windows 7, Server 2003/2008 R2, Novell NetWare, Linux, Mac ex OS 10.4	Windows XP, Vista, Windows 7, Server 2003/2008 R2, Novell NetWare, Linux, Mac ex OS 10.4
	Emulations	PCL6, KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6, KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc
NETWORK	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host, CF slot	USB 2.0, 10/100/1000BaseTX, USB host, CF slot
	Network protocols	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk
	Operating systems	Windows XP, Vista, Windows 7, Server 2003/2008 R2	Windows XP, Vista, Windows 7, Server 2003/2008 R2
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP
FAX	Originals	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	100/2,000	100/2,000

# A4 MULTIFUNCTIONAL SYSTEMS



		CDC 5526L	CDC 5626L	CDC 5526	CDC 5626
COPYING	Copy speed	26 A4 pages/min. in colour and b/w	26 A4 pages/min. in colour and b/w	26 A4 pages/min. in colour and b/w	26 A4 pages/min. in colour and b/w
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256	256
	Standard paper feed	300 (1 x 250 + 50 sheets)	300 (1 x 250 + 50 sheets)	300 (1 x 250 + 50 sheets)	300 (1 x 250 + 50 sheets)
	Optional paper feed	2 x 500 sheets	2 x 500 sheets	2 x 500 sheets	2 x 500 sheets
	Paper capacity, max	1,300 sheets	1,300 sheets	1,300 sheets	1,300 sheets
	Paper format	A6R-A4	A6R-A4	A6R-A4	A6R-A4
	Original feeder	Standard	Standard	Standard	Standard
	Duplex	Standard	Standard	Standard	Standard
	System memory	768 MB RAM, max 1,792 MB RAM	768 MB RAM, max 1,792 MB RAM	1,024 MB RAM, max 2,048 MB RAM	1,024 MB RAM, max 2,048 MB RAM
	Zoom	25%-400%	25%-400%	25%-400%	25%-400%
Cabinet	Option: no. 61	Option: no. 61	Option: no. 61	Option: no. 61	
PRINTING	Type	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100BaseTX, USB host (2), CF slot	USB 2.0, 10/100BaseTX, USB host (2), CF slot	USB 2.0, 10/100BaseTX, USB host (2), CF slot	USB 2.0, 10/100/1000 BaseTX, USB host (2), CF slot
	Operating systems	Windows 2000, XP, Vista, Windows 7, Server 2000/2003/2008 R2, Novell NetWare, Linux, Mac ex OS 10.4	Windows 2000, XP, Vista, Windows 7, Server 2000/2003/2008 R2, Novell NetWare, Linux, Mac ex OS 10.4	Windows 2000, XP, Vista, Windows 7, Server 2000/2003/2008 R2, Novell NetWare, Linux, Mac ex OS 10.4	Windows 2000, XP, Vista, Windows 7, Server 2000/2003/2008 R2, Novell NetWare, Linux, Mac ex OS 10.4
	Emulations	PCL6, KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.5, XPS	PCL6, KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.5, XPS	PCL6, KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.5, XPS	PCL6, KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.5, XPS
NETWORK	Interfaces	10/100BaseTX	10/100BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TC P/IP, IPX/SPX, Net BEUI, EtherTalk
	Operating systems	Windows XP, Vista, Windows 7, Server 2003/2008 R2	Windows XP, Vista, Windows 7, Server 2003/2008 R2	Windows XP, Vista, Windows 7, Server 2003/2008 R2	Windows XP, Vista, Windows 7, Server 2003/2008 R2
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100BaseTX	10/100BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	Originals		max A4		max A4
	Modem speed		33.6 kbps		33.6 kbps
	Compression method		JBIG, MMR, MR, MH		JBIG, MMR, MR, MH
	One-touch dial/abbr. dial		22/100		100/200

## A3 PRINT SYSTEM



### CLP 3550

Print format	A6R-A3
Print speed	50/55 A4 pages/min. in colour and b/w, 25/28 A3 pages/min. in colour and b/w
Print resolution	600 x 600 dpi
Standard paper feed	1,100 (2 x 500 + 100 sheets)
Optional paper feed	2 x 500 sheets, 3,000 sheets
Duplex	Standard
Processor	PowerPC 750GL/750 MHz
Print memory	1,024 MB + 160 GB
Interfaces	USB 2.0, 10/100BaseTX, USB host, CF slot
Network card optional	--
Emulations	PCL6, KPDL 3 (PS 3 compatible), XPS, PRESCRIBE IIc

# A4 PRINT SYSTEMS



	CLP 3721	CLP 3726	CLP 3630	CLP 3635
Print format	A6R-A4	A6R-A4	A6R-A4	A6R-A4
Print speed	21 A4 pages/min. in colour and b/w	26 A4 pages/min. in colour and b/w	30 A4 pages/min. in colour and b/w	35 A4 pages/min. in colour and b/w
Print resolution	600 x 600 dpi, up to 9,600 dpi level x 600 dpi	600 x 600 dpi, up to 9,600 dpi level x 600 dpi	600 x 600 dpi, up to 9,600 dpi level x 600 dpi	600 x 600 dpi, up to 9,600 dpi level x 600 dpi
Standard paper feed	300 (1 x 250 + 50 sheets)	550 (1 x 500 + 50 sheets)	650 (1 x 500 + 150 sheets)	650 (1 x 500 + 150 sheets)
Optional paper feed	2 x 500 sheets	3 x 500 sheets	3 x 500 sheets	4 x 500 sheets
Duplex	Standard	Standard	Standard	Standard
Processor	PowerPC 464/667 MHz	PowerPC 464/667 MHz	PowerPC 750CL/600 MHz	PowerPC 750FL/733 MHz
Print memory	256 MB (max 1,280 MB)	256 MB (max 1,280 MB)	256 MB (max 1,280 MB)	256 MB (max 1,280 MB)
Interfaces	USB 2.0, 10/100BaseTX, USB host	USB 2.0, 10/100BaseTX, USB host	USB 2.0, 10/100BaseTX, USB host, CF slot	USB 2.0, 10/100BaseTX, USB host, CF slot
Network card optional	--	--	--	--
Emulations	PCL6, KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6, KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6, KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6, KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc

# A3 MULTIFUNCTIONAL SYSTEMS



		CD 5025/P	CD 5030
COPYING	Copy speed	25 A4 pages/min., 12 A3 pages/min.	30 A4 pages/min., 15 A3 pages/min.
	Copy resolution	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256
	Standard paper feed	600 (500 + 100 sheets)	600 (500 + 100 sheets)
	Optional paper feed	1 or 2 x 500 sheets	1 or 2 x 500 sheets
	Paper capacity, max	1,600 sheets	1,600 sheets
	Paper format	A6R–A3	A6R–A3
	Original feeder	CD 5025: standard CD 5025P: platen cover	Standard
	Duplex	Standard	Standard
	System memory	512 MB (max 1,536 MB)	512 MB (max 1,536 MB)
	Zoom	25%–400%	25%–400%
	Cabinet	Option: no. 62	Option: no. 62
PRINTING	Type	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2), CF slot	USB 2.0, 10/100/1000BaseTX, USB host (2), CF slot
	Operating systems	Windows XP, Vista, Windows 7, Server 2003/ 2008 R2, Novell NetWare, Linux, Mac OS 10.x	Windows XP, Vista, Windows 7, Server 2003/ 2008 R2, Novell NetWare, Linux, Mac OS 10.x
	Emulations	PCL6, KPDL 3 (PS 3 compatible), XPS, PRESCRIBE IIc	PCL6, KPDL 3 (PS 3 compatible), XPS, PRESCRIBE IIc
NETWORK	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk
	Operating systems	Windows XP, Vista, Windows 7, Server 2003/ 2008 R2	Windows XP, Vista, Windows 7, Server 2003/ 2008 R2
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP
FAX	Originals	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	100/200	100/200

# A3 MULTIFUNCTIONAL SYSTEMS



		CD 1118	CD 1218	CD 1222
COPYING	Copy speed	18 A4 pages/min., 8 A3 pages/min.	18 A4 pages/min., 8 A3 pages/min.	22 A4 pages/min., 10 A3 pages/min.
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256
	Standard paper feed	400 (1 x 300 + 100 sheets)	400 (1 x 300 + 100 sheets)	700 (2 x 300 + 100 sheets)
	Optional paper feed	3 x 300 sheets	3 x 300 sheets	2 x 300 sheets
	Paper capacity, max	1,300 sheets	1,300 sheets	1,300 sheets
	Paper format	A6R-A3	A6R-A3	A6R-A3
	Original feeder	Option: DP-420	Option: DP-420	Option: DP-420
	Duplex	Option: DU-420	Option: DU-420	Option: DU-420
	System memory	32 MB (max 160 MB)	64 MB (max 192 MB)	64 MB (max 192 MB)
	Zoom	25%–400%	25%–400%	25%–400%
Cabinet	Option: high no. 57, low no. 58	Option: high no. 57, low no. 58	Option: high no. 57, low no. 58	
PRINTING	Type	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0	10/100BaseTX, USB 2.0, CF slot	10/100BaseTX, USB 2.0, CF slot
	Operating systems	Windows XP, Vista	Windows XP, Vista, Windows 7, Server 2003/2008, Novell NetWare, Linux, Mac OS X	Windows XP, Vista, Windows 7, Server 2003/2008, Novell NetWare, Linux, Mac OS X
	Emulations	GDI	PCL6, KPDL 3 (PS 3 compatible), Line Printer, Diablo 630, Epson LQ-850, IBM Proprinter X24E, KCGL, PRESCRIBE IIe	PCL6, KPDL 3 (PS 3 compatible), Line Printer, Diablo 630, Epson LQ-850, IBM Proprinter X24E, KCGL, PRESCRIBE IIe
NETWORK	Interfaces	Network adapter	10/100BaseTX	10/100BaseTX
	Network protocols	TCP/IP	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk
	Operating systems	Windows XP, Vista	Windows XP, Vista, Windows 7, Server 2003/2008 R2	Windows XP, Vista, Windows 7, Server 2003/2008 R2
SCAN	Scan type		CCD b/w	CCD b/w
	Scan resolution		200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces		10/100BaseTX	10/100BaseTX
	Network protocols		TCP/IP	TCP/IP
FAX	Originals		max A3	max A3
	Modem speed		33.6 kbps	33.6 kbps
	Compression method		JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial		32/200	32/200

# A3 MULTIFUNCTIONAL SYSTEMS



		CD 1435	CD 1445	CD 1455
COPYING	Copy speed	35 A4 pages/min., 17 A3 pages/min.	45 A4 pages/min., 22 A3 pages/min.	55 A4 pages/min. and 27 A3 pages/min.
	Copy resolution	600 x 600 dpi, 9,600 x 600 dpi level	600 x 600 dpi, 9,600 x 600 dpi level	600 x 600 dpi, 9,600 x 600 dpi level
	Greyscales	256	256	256
	Standard paper feed	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)
	Optional paper feed	2 x 500, 3,000 sheets, different combinations possible	2 x 500, 3,000 sheets, different combinations possible	2 x 500, 3,000 sheets, different combinations possible
	Paper capacity, max	7,150 sheets	7,150 sheets	7,150 sheets
	Paper format	A6R-A3+	A6R-A3+	A6R-A3+
	Original feeder	Option: DP-770 or DP-771	Option: DP-770 or DP-771	Option: DP-770 or DP-771
	Duplex	Standard	Standard	Standard
	System memory	1,024 (max 2,048) MB RAM + 160 GB	1,024 (max 2,048) MB RAM + 160 GB	1,024 (max 2,048) MB RAM + 160 GB
	Zoom	25%–400%	25%–400%	25%–400%
	Cabinet	Option: no. 63	Option: no. 63	Option: no. 63
	PRINTING	Type	Integrated within the system	Integrated within the system
Interfaces		USB 2.0, 10/100/1000BaseTX, USB host, CF slot	USB 2.0, 10/100/1000BaseTX, USB host, CF slot	USB 2.0, 10/100/1000BaseTX, USB host, CF slot
Operating systems		Windows XP, Vista, Windows 7, Server 2003/2008 R2, Novell NetWare, Linux, Mac ex OS 10.4	Windows XP, Vista, Windows 7, Server 2003/2008 R2, Novell NetWare, Linux, Mac ex OS 10.4	Windows XP, Vista, Windows 7, Server 2003/2008 R2, Novell NetWare, Linux, Mac ex OS 10.4
Emulations		PCL6, KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe	PCL6, KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe	PCL6, KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe
NETWORK	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host, CF slot	USB 2.0, 10/100/1000BaseTX, USB host, CF slot	USB 2.0, 10/100/1000BaseTX, USB host, CF slot
	Network protocols	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk
	Operating systems	Windows XP, Vista, Windows 7, Server 2003/2008 R2	Windows XP, Vista, Windows 7, Server 2003/2008 R2	Windows XP, Vista, Windows 7, Server 2003/2008 R2
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP	TCP/IP
FAX	Originals	max A3	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	100/2,000	100/2,000	100/2,000

## A3 MULTIFUNCTIONAL SYSTEMS



		CD 1465	CD 1480
COPYING	Copy speed	65 A4 pages/min., 32 A3 pages/min.	80 A4 pages/min., 40 A3 pages/min.
	Copy resolution	600 x 600 dpi, 9,600 x 600 dpi level	600 x 600 dpi, 9,600 x 600 dpi level
	Greyscales	256	256
	Standard paper feed	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)
	Optional paper feed	2 x 500, 3,000 sheets, different combinations possible	2 x 500, 3,000 sheets, different combinations possible
	Paper capacity, max	7,650 Blatt	7,650 Blatt
	Paper format	A6R–A3+	A6R–A3+
	Original feeder	Standard	Standard
	Duplex	Standard	Standard
	System memory	2,048 MB RAM, 2 x 160 GB	2,048 MB RAM, 2 x 160 GB
	Zoom	25%–400%	25%–400%
	Cabinet	--	--
PRINTING	Type	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host, CF slot	USB 2.0, 10/100/1000BaseTX, USB host, CF slot
	Operating systems	Windows XP, Vista, Windows 7, Server 2003/2008 R2, Novell NetWare, Linux, Mac OS 10.4	Windows XP, Vista, Windows 7, Server 2003/2008 R2, Novell NetWare, Linux, Mac OS 10.4
	Emulations	PCL6, KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe	PCL6, KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe
NETWORK	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host, CF slot	USB 2.0, 10/100/1000BaseTX, USB host, CF slot
	Network protocols	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk
	Operating systems	Windows XP, Vista, Windows 7, Server 2003/2008 R2	Windows XP, Vista, Windows 7, Server 2003/2008 R2
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP
FAX	Originals	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	100/2,000	100/2,000

# A3 MULTIFUNCTIONAL SYSTEMS



		CD 5130/P	CD 5230	CD 5135	CD 5235
COPYING	Copy speed	30 A4 pages/min.	30 A4 pages/min.	35 A4 pages/min.	35 A4 pages/min.
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256	256
	Standard paper feed	300 (1 x 250 + 50 sheets)	300 (1 x 250 + 50 sheets)	300 (1 x 250 + 50 sheets)	300 (1 x 250 + 50 sheets)
	Optional paper feed	2 x 250 sheets	2 x 250 sheets	2 x 250 sheets	2 x 250 sheets
	Paper capacity, max	800 sheets	800 sheets	800 sheets	800 sheets
	Paper format	A6R–A4	A6R–A4	A6R–A4	A6R–A4
	Original feeder	CD 5130: standard CD 5130P: platen cover	Standard	Standard	Standard
	Duplex	Standard	Standard	Standard	Standard
	System memory	256 MB (max 768 MB)	256 MB (max 768 MB)	256 MB (max 768 MB)	256 MB (max 768 MB)
	Zoom	25%–400%	25%–400%	25%–400%	25%–400%
	Cabinet	Option: no. 64	Option: no. 64	Option: no. 64	Option: no. 64
	PRINTING	Type	Integrated within the system	Integrated within the system	Integrated within the system
Interfaces		10/100BaseTX, USB 2.0, USB host, CF slot	10/100BaseTX, USB 2.0, USB host, CF slot	10/100BaseTX, USB 2.0, USB host, CF slot	10/100BaseTX, USB 2.0, USB host, CF slot
Operating systems		Windows XP, Vista, Windows 7, Server 2003/ 2008 R2, Novell NetWare, Linux, Mac ex OS X	Windows XP, Vista, Windows 7, Server 2003/ 2008 R2, Novell NetWare, Linux, Mac ex OS X	Windows XP, Vista, Windows 7, Server 2003/ 2008 R2, Novell NetWare, Linux, Mac ex OS X	Windows XP, Vista, Windows 7, Server 2003/ 2008 R2, Novell NetWare, Linux, Mac ex OS X
Emulations		PCL6, KPDL 3 (PS 3 compatible), PRESCRIBE IIe, Line Printer, Diablo 630, IBM Proprinter X24E, Epson LQ-850, PDF 1.5, XPS (additional memory required)	PCL6, KPDL 3 (PS 3 compatible), PRESCRIBE IIe, Line Printer, Diablo 630, IBM Proprinter X24E, Epson LQ-850, PDF 1.5, XPS (additional memory required)	PCL6, KPDL 3 (PS 3 compatible), PRESCRIBE IIe, Line Printer, Diablo 630, IBM Proprinter X24E, Epson LQ-850, PDF 1.5, XPS (additional memory required)	PCL6, KPDL 3 (PS 3 compatible), PRESCRIBE IIe, Line Printer, Diablo 630, IBM Proprinter X24E, Epson LQ-850, PDF 1.5, XPS (additional memory required)
NETWORK	Interfaces	10/100BaseTX	10/100BaseTX	10/100BaseTX	10/100BaseTX
	Network protocols	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk
	Operating systems	Windows XP, Vista, Windows 7, Server 2003/ 2008 R2	Windows XP, Vista, Windows 7, Server 2003/ 2008 R2	Windows XP, Vista, Windows 7, Server 2003/ 2008 R2	Windows XP, Vista, Windows 7, Server 2003/ 2008 R2
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100BaseTX, USB 2.0	10/100BaseTX, USB 2.0	10/100BaseTX, USB 2.0	10/100BaseTX, USB 2.0
	Network protocols	TCP/IP, IPX/SPX, EtherTalk	TCP/IP, IPX/SPX, EtherTalk	TCP/IP, IPX/SPX, EtherTalk	TCP/IP, IPX/SPX, EtherTalk
FAX	Originals		max A4		max A4
	Modem speed		33.6 kbps		33.6 kbps
	Compression method		JBIG, MMR, MR, MH		JBIG, MMR, MR, MH
	One-touch dial/abbr. dial		22/100		22/100

# A4 MULTIFUNCTIONAL SYSTEMS



		CD 5140L	CD 5240L	CD 5140	CD 5240
COPYING	Copy speed	40 A4 pages/min.	40 A4 pages/min.	40 A4 pages/min.	40 A4 pages/min.
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256	256
	Standard paper feed	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	Optional paper feed	3 x 500 sheets	3 x 500 sheets	3 x 500 sheets	3 x 500 sheets
	Paper capacity, max	2,100 sheets	2,100 sheets	2,100 sheets	2,100 sheets
	Paper format	A6R-A4	A6R-A4	A6R-A4	A6R-A4
	Original feeder	Standard	Standard	Standard	Standard
	Duplex	Standard	Standard	Standard	Standard
	System memory	256 MB RAM, max 768 MB RAM	256 MB RAM, max 768 MB RAM	1,024 MB RAM, max 2,048 MB RAM	1,024 MB RAM, max 2,048 MB RAM
	Zoom	25%–400%	25%–400%	25%–400%	25%–400%
Cabinet	Option: high no. 64, low no. 65	Option: high no. 64, low no. 65	Option: high no. 64, low no. 65	Option: high no. 64, low no. 65	
PRINTING	Type	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	10/100BaseTX, USB 2.0, USB host, CF slot	10/100BaseTX, USB 2.0, USB host, CF slot	USB 2.0, 10/100/1000BaseTX, USB host (2), CF slot	USB 2.0, 10/100/1000BaseTX, USB host (2), CF slot
	Operating systems	Windows 2000, XP, Vista, Windows 7, Server 2000/2003/2008 R2, Novell NetWare, Linux, Mac OS 10.4	Windows 2000, XP, Vista, Windows 7, Server 2000/2003/2008 R2, Novell NetWare, Linux, Mac OS 10.4	Windows 2000, XP, Vista, Windows 7, Server 2000/2003/2008 R2, Novell NetWare, Linux, Mac OS 10.4	Windows 2000, XP, Vista, Windows 7, Server 2000/2003/2008 R2, Novell NetWare, Linux, Mac OS 10.4
	Emulations	PCL6, KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630, PDF 1.5, XPS (additional memory required)	PCL6, KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630, PDF 1.5, XPS (additional memory required)	PCL6, KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630, PDF 1.5, XPS (additional memory required)	PCL6, KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630, PDF 1.5, XPS (additional memory required)
NETWORK	Interfaces	10/100BaseTX	10/100BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk	TCP/IP, IPX/SPX, Net BEUI, EtherTalk
	Operating systems	Windows XP, Vista, Windows 7, Server 2003/2008 R2	Windows XP, Vista, Windows 7, Server 2003/2008 R2	Windows XP, Vista, Windows 7, Server 2003/2008 R2	Windows XP, Vista, Windows 7, Server 2003/2008 R2
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100BaseTX, USB 2.0	10/100BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	Originals		max A4		max A4
	Modem speed		33.6 kbps		33.6 kbps
	Compression method		JBIG, MMR, MR, MH		JBIG, MMR, MR, MH
	One-touch dial/abbr. dial		22/100		100/200

## A3 PRINT SYSTEM



### LP 3151

Print format	A6R-A3
Print speed	51 A4 pages/min., 26 A3 pages/min.
Print resolution	1,200 x 1,200 dpi
Standard paper feed	1,200 (2 x 500 + 200 sheets)
Optional paper feed	2 x 500, 3,000 sheets
Duplex	Standard
Processor	PowerPC 750FL/600 MHz
Print memory	128 MB (max 640 MB)
Interfaces	IEEE 1284 parallel, USB 2.0, 10/100BaseTX, CF slot
Network card optional	--
Emulations	PCL6, KPDL 3 (PS 3 compatible), Line Printer, Diablo 630, Epson LQ-850, IBM Proprinter X24E, KCGL, PRESCRIBE IIe

# A4 PRINT SYSTEMS



## LP 3130

Print format	A6R-A4	LP 3135	A6R-A4	LP 3335	A6R-A4
Print speed	30 A4 pages/min.	35 A4 pages/min.	35 A4 pages/min.		
Print resolution	600 x 600 dpi	600 x 600 dpi	1,200 x 1,200 dpi		
Standard paper feed	250 + 50 sheets	250 + 50 sheets	250 + 50 sheets		
Optional paper feed	1 x 250 sheets	2 x 250 sheets	2 x 250 sheets		
Duplex	Standard	Standard	Standard		
Processor	PowerPC 405F5/360 MHz	PowerPC 405F5/360 MHz	PowerPC 440F5/500 MHz		
Print memory	32 MB (max 544 MB)	32 MB (max 544 MB)	128 MB (max 1,152 MB)		
Interfaces	USB 2.0, CF slot	USB 2.0, CF slot	USB 2.0, 10/100BaseTX, USB host, CF slot		
Network card optional	100BaseTX/1000BaseT	100BaseTX/1000BaseT	--		
Emulations	PCL6, KPDL 3 (PS 3 compatible), Line Printer, Diablo 630, Epson LQ-850, IBM Proprinter X24E, KCGL, PRESCRIBE IIe	PCL6, KPDL 3 (PS 3 compatible), Line Printer, Diablo 630, Epson LQ-850, IBM Proprinter X24E, KCGL, PRESCRIBE IIe	PCL6, KPDL 3 (PS 3 compatible), Line Printer, Diablo 630, Epson LQ-850, IBM Proprinter X24E, PRESCRIBE IIe, PDF 1.5, XPS		



## LP 3235

Print format	A6R-A4
Print speed	35 A4 pages/min.
Print resolution	1,200 x 1,200 dpi
Standard paper feed	500 + 100 sheets
Optional paper feed	1 x 500 sheets
Duplex	Standard
Processor	PowerPC 440F5/533 MHz
Print memory	128 MB (max 1,152 MB)
Interfaces	USB 2.0, USB host, CF slot
Network card optional	100BaseTX/1000BaseT
Emulations	PCL6, KPDL 3 (PS 3 compatible), Line Printer, Diablo 630, Epson LQ-850, IBM Proprinter X24E, PRESCRIBE IIe, PDF 1.5, XPS



## LP 3240

Print format	A6R-A4	LP 3245	A6R-A4
Print speed	40 A4 pages/min.	45 A4 pages/min.	
Print resolution	1,200 x 1,200 dpi	1,200 x 1,200 dpi	
Standard paper feed	500 + 100 sheets	500 + 100 sheets	
Optional paper feed	3 x 500, 2,000 sheets	3 x 500, 2,000 sheets	
Duplex	Standard	Standard	
Processor	PowerPC 440F5/600 MHz	PowerPC 750/667 MHz	
Print memory	128 MB (max 1,152 MB)	128 MB (max 1,152 MB)	
Interfaces	IEEE 1284 parallel, USB 2.0, USB host, 10/100BaseTX, CF slot	IEEE 1284 parallel, USB 2.0, USB host, 10/100BaseTX, CF slot	
Network card optional	--	--	
Emulations	PCL6, KPDL 3 (PS 3 compatible), Line Printer, Diablo 630, Epson LQ-850, IBM Proprinter X24E, PRESCRIBE IIe, PDF 1.5, XPS	Epson LQ-850, IBM Proprinter X24E, PRESCRIBE IIe, PDF 1.5	

# LARGE FORMAT COPY/PLOT SYSTEMS



**XC 9124**

Copy speed	2.4 meter/min.
Copy/print resolution	600 x 600 dpi
Standard paper feed	1 roll + single sheet feed
Paper output	To the bottom
Paper format	min 297 x 210 mm, max 914 x 2,400 mm
Scan format	min 297 x 210 mm, max 914 x 6,000 mm
Warm-up time	2.5 minutes
Continuous copying	1-999 copies
Zoom	25%-400%
Cabinet	--
Options	b/w & colour scan, colour copier (needs b/w & colour scan option), PDF/PostScript Level 3, paper tray kit for 20 sheets (A4 up to A2)



**XC 9148**

Copy speed	4.8 meter/min.
Copy/print resolution	600 x 600 dpi
Standard paper feed	2 rolls + single sheet feed
Paper output	To the back, to the top
Paper format	min 297 x 210 mm, max 914 x 6,000 mm
Scan format	min 297.4 x 210 mm, max 914.4 x 6,000 mm
Warm-up time	4.5 minutes
Continuous copying	1-999 copies
Zoom	5%-3,600%
Cabinet	--
Options	b/w & colour scan, colour copier (needs b/w & colour scan option), PDF/PostScript Level 3, paper tray kit for 50 sheets (A4 up to A2), tray for originals and copies/prints

# PRODUCT OVERVIEW 12/2011

## Your UTAX dealer

Since 1961 UTAX GmbH has been a brand for professional office technology. As a partner to retailers and medium-sized companies, we specialise in sales and integration of printing, copying and multifunctional systems in business IT. When advising our customers, we always strive to support their strategic business objectives with UTAX solutions. In addition to hardware, UTAX also develops customized software for efficient document management.

UTAX GmbH Norderstedt  
[www.utax.com](http://www.utax.com)

UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trademarks of UTAX GmbH. All other brand names referred to are registered trademarks of the respective manufacturers.